ingenico

MOVE/5000

The perfect companion for mobile businesses, indoors and out





Designed for hospitality, high street and small merchants, the Move/5000 enables a seamless shopping experience that's free from the checkout.

3.5" color touchscreen and ergonomic interface

Payments anywhere and anytime

• 4G, 3G, GPRS, Dual SIM, Bluetooth and WiFi

All methods of payment accepted

• EMV Chip & PIN, contactless, magstripe or digital wallets and QR-code based payments

Fast integrated printer

Raising the bar on security with PCI PTS V6

Powerful high-end optional features

- 1D/2D barcode scanner
- 5M rear camera (up to 8MP)

Long-lasting battery for the lengthy working day (up to 3100mAh)



- Professional services

Specifications

OS		Telium TETRA	~
Memory	InternalExternal	512 MB Flash, 512 MB RAMMicroSD up to 32GB	×
Processor	 Application & Crypto processor 	Cortex A5	~
Card readers	MagstripeSmart cardNFC/Contactless	 ISO 1/2/3, 500K lifespan EMV Level 1, 500K lifespan EMV Contactless L1 3.0 certified 	× × ×
SIM		1 SIM2 SIM	Option ✓
SAM		2 SAM3 SAM	∽ Option
Data Capture	PositioningBarcode readerCamera	 GPS tracking 1D/2D 5M pixels autofocus 	Option Option Option
Display	Colour	 3.5" backlit, HVGA (480x320 pixels) 	~
Touchscreen	 Resistive Capacitive		✓ Option
Keypad		 16 keys, raised marking, backlit 	~
Audio	BuzzerSpeakerAudio Jack	• Mono • Stereo	✓ Option Option
Video	Video accelerator	• H264 codec	~

Thermal Printer	Speed in lines/sPaper roll cage	 up to 30 lines/s 58 mm width x Ø 40 mm 58 mm width x Ø 25 mm 	∽ ∽ Option
Terminal Connectivity	WANLANMulticom	 4G and/or 3G with fallback WiFi and/or Bluetooth WAN + LAN 	Option Option Option
Terminal Connections	USBPower Supply	Host & SlaveDedicated power Jack	~
Battery	• Li-ion	 2200mAh 3100mAh	Option ✓
Terminal Size	 Ø 40 mm Ø 25 mm 	 169x78x57 mm (6.6x3.1x2.2") 160x78x47 mm (6.3x3.1x1.9") 	~
Weight	 Terminal + battery 	• 320 g (11 oz)	~
Security		 PCI PTS 6.online & offline certified 	~
Environment	 Operating temperature Storage temperature Operating humidity 	 -10°C to +50°C (14°F to 122°F) -20°C to +55°C (-4°F to 131°F) 85% non-condensing at +40°C (104°F) 	× × ×
Accessory	 Privacy shield Car Charger Docking-station Stylus Kit 	 Factory Mounted Charger 2 R\$232 USB Host USB Slave Modem Ethernet 10/100 Base T Bluetooth 	Option Option Option Option Option Option Option Option

